



ALPINE SANITATION & SUPPLIES LTD.

24 Ronson Drive, Unit 16, Etobicoke, Ontario M9W 1B4

Bus: (416)-744-2120 Fax: (416)-249-1859 Toll Free: 1-800 465-6198

GT SERIES DISHMACHINES – BEST IN VALUE

Performance is everything in a busy kitchen and your customers depend on reliable dishmachines that won't breakdown. Knight sets the standard for warewash technology with our high quality, attractively priced, low energy GT dishmachine line – which is unquestionably the best value in the industry. The KLE-175 GT upright and KLE-150 GT undercounter dishmachines are quality engineered and manufactured with field proven parts and materials. As a result, your customers get uncompromised reliability and exceptional uptime performance, year after year.

The GT Series offer reliable performance and attractive pricing structures that will satisfy your customers and give you higher returns on your investment. The GT dishmachines deliver consistent, high pressure cleaning power with a 1 HP high efficiency motor and advanced recirculating pump with open impeller. Other value-added features include: microprocessor control with four cycle time selections, chemical feed pumps with exclusive long-life squeeze tubes, high performance upper and lower spray arms, #304 stainless steel construction, and more. That's why world-leading chemical suppliers and restaurant equipment distributors chose Knight's GT dishmachines.



KLE-175 GT

KLE-175 GT UPRIGHT

The KLE-175 GT upright can clean up to 46 racks per hour and is perfect for restaurants and fast food operations. KLE-175 GT can be configured for straight-through or corner operation. This all-inclusive dishmachine even comes with a convenient water connection point and an electrical supply hook-up terminal for other kitchen chemical dispensers, saving you precious time and space.



- Straight-Through or Corner Configuration
- Microprocessor Based Electronic Control With 72, 90, 120 or 360 Second Wash Cycles
- Built-in Chemical Metering Pumps – Detergent, Sanitizer, Rinse
- Automatic Start/Stop
- Convenient Drain/Fill Switch
- Active Wash Cycle LED Light
- Water Connection Point for Water Driven Dispensing Systems such as Sink Mate and Sink Bowl
- 14 Gauge #304 Stainless Steel Construction
- Front or Side Accessible Scrap Trap
- Open Impeller with Pause Cycle
- Internal Pump Screen
- Electronic Dispenser Power Terminal

COMPACT BOOSTER WATER HEATER
Clean and sanitize with really hot water. This booster heater offers 180° rinse water for fast, safe and efficient cleaning.



WATER CONNECTION POINT



BUILT-IN POWER TERMINAL



| MODEL | PART # | DESCRIPTION |
|------------|------------|--|
| KLE-175 GT | 9000175-01 | KLE-175GT dishmachine, straight or corner convertible, single rack. 120V 60Hz. |
| KLE-175 GT | 9000175-03 | KLE-175GT dishmachine, straight or corner convertible, single rack. 240V 50/60Hz. |
| KLE-175 GT | 9000175-H1 | KLE-175GT dishmachine with factory installed tank heater. 120V 60Hz. |
| KLE-175 GT | 9000175-P1 | KLE-175GT dishmachine with factory installed pump out drain. 120V 60Hz. |
| KLE-175 GT | 9000175PH1 | KLE-175GT dishmachine with factory installed tank heater and pump out drain 120V 60Hz. |
| KLE-175 GT | 9641739 | Compact booster water heater. |
| KLE-175 GT | 7120113 | Mounting bracket for 1 or 2 chemical dispensers. |
| | 7501318 | Low level alarm/proof of delivery installation kit. |



Operating Capacity: Racks Per Hour
 Wash Time:
 Rinse Time:
 Drain Time:
 Wash Tank Capacity:
 Wash Pump Capacity:
 Recommended Wash Temperature:
 Water Inlet:
 Drain I.P.S.:
 Wash Pump Motor:
 Dimensions:
 Table Height:
 Max. Clearance For Dishes:
 Standard Dish Rack:
 Shipping Weight:
 Electrical Rating:
 Load Amps:

| | <u>90 Sec.</u> | <u>120 Sec.</u> |
|---------------------------|----------------|-----------------|
| 46 | 37 | 30 |
| 37 Sec. | 45 Sec. | 55 Sec. |
| 24 Sec. | 30 Sec. | 50 Sec. |
| 11 Sec. | 15 Sec. | 15 Sec. |
| 1.75 Gallons | | |
| 57 GPM | | |
| 140 Degrees | | |
| 3/4" | | |
| 1.5" | | |
| 1 HP | | |
| 25.5" D x 25.5" W x 67" H | | |
| 34" | | |
| 17" | | |
| 20" x 20" | | |
| 200 Pounds | | |
| 120V 60Hz, 240V 50/60Hz | | |
| 14, 7 | | |

